

PRO-VAC SEALANT TAPES

Next generation vacuum bagging sealant tapes

Description:

- Improved level of tack and hand ability.
- Tape performs best at room temperature (+ 20°C), if the tape is too cold the tack levels will be dramatically reduced.
- Recommended for use in vacuum infusion, wet lay-up bagging and bag to bag (envelope bagging) processing.
- Compatible with most vacuum films and tool surfaces but pre-production trials are advisable.
- We recommend that the tape is removed from the mould at room temperature.



Technical data:

	PRO-VAC B1191	PRO-VAC B1192	PRO-VAC W1200	PRO-VAC G1191
Max use temperature	150°C	150°C	150°C	150°C
Colour	Black	Black	White (less tack)	Grey
Standard roll size	3 mm x 12 mm x 15 m	2mm x 10mm x 22.5m	3mm x 12mm x 15m	3mm x 12mm x 15m
Standard packaging	22 rolls per box	22 rolls per box	22 rolls per case	22 rolls per case

*The tape can also be supplied various other flat dimensions as well as a double strip profile and a bead in various diameters

Packaging and storage

Store in original and unopened packaging and protected from humidity.
 Store at a maximum temperature of 30°C in a ventilated environment.
 Material has a 12 months shelf life from date of manufacture.
 Store flat with a maximum of 5 boxes stacked.



HF Industri & Marine^{ApS}

HF Industri & Marine ApS Gotlandsvej 6 5700 Svendborg Denmark
 Phone: +45 62 20 13 12 • Fax: +45 62 20 14 77 • info@hfmarine.dk • www.hfmarine.dk

All statements, technical information and recommendations, including storage, contained in this publication are based on tests believed to be reliable, but their accuracy and/or completeness are not guaranteed. The user shall determine the suitability of this particular purpose and shall assume all risk and liability in connection herewith.